

Corpo illuminante da parete da esterno. Design minimale ed elegante. Dimensioni ridotte e orientabile. Emissione diretta.

Wall-mounted luminaire for outdoor use. Minimal and elegant design. Small size and adjustable. Direct issue.

# DEAR IP BASE




18°




27°



40°



EL



## FINITURE / FINISHES

Nero / Black RAL 9005	<b>NR</b>	<b>BN</b>	Bianco / White RAL 9016
Antracite / Anthracite	<b>AT</b>	<b>MK</b>	Moka
Corten	<b>CT</b>	<b>RM</b>	Rame / Copper
Ottone / Brass	<b>OT</b>	<b>AL</b>	Alluminio / Aluminium
Ottone brunito / Burnished brass	<b>OTBR</b>	<b>TT</b>	Titanio L55 / Titanium L55 Galvanica / Galvanic
Anodizzato Nero / Anodized black	<b>AN</b>	<b>AA</b>	Anodizzato Alluminio / Anodized aluminium
Anodizzato Bronzo / Anodized bronze	<b>BRS</b>	<b>AC</b>	Anodizzato Champagne / Anodized champagne
Cromo lucido / Polished chrome	<b>CR</b>	<b>OR</b>	Oro lucido / Shiny gold
Oro satinato / Satin gold	<b>ORST</b>	<b>ORM</b>	Oro rame / Copper gold
		<b>CS</b>	Custom

Code	XX (LED Color)	YY° (Optic)	ZZ (Power)	Flux
	HW (2700K)	18		
DEABSIP	WW (3000K)	27	O3 (3 W)	366 lm
	NN (4000K)	40	O4 (4,5 W)	508 lm
		EL [20+42]		

## MATERIALI / MATERIALS


Corpo in alluminio tornito dal pieno, verniciabile in un'ampia gamma di colori.

Aluminum body turned from solid, paintable in a wide range of colors.

## ELETTRONICA / ELECTRONICS

Led ad alto rendimento. Dimmerabile remoto DALI, PUSH, DMX, 0-10, 1-10 e TAGLIO DI FASE.

High performance LED. Remote dimmable DALI, PUSH, DMX, 0-10, 1-10 and PHASE CUT.



Accessorio cover anti-abbagliamento  
Anti-glare cover accessory