

Corpo illuminante per micro binario bassa tensione, cilindrico orientabile a 90° sull'asse trasversale e a 355° sull'asse longitudinale. Dimensioni compatte. Emissione diretta. Verniciabile in un'ampia gamma di colori.

Lighting body for low voltage micro track, cylindrical, adjustable at 90° on the transverse axis and at 355° on the longitudinal axis. Compact size. Direct issue. Paintable in a wide range of colors.

DEAR MICRO

BT

PL pag. 82 TC pag. 116 **BT** pag. 173




18°




27°



40°



EL



Code	XX (LED Color)	YY° (Optic)	ZZ (Power)	Flux
	HW (2700K)	18		
	WW (3000K)	27	03 (3 W)	
DEAMBTT	NN (4000K)	40	04 (4,5 W)	366 lm
		EL [20+44]		

FINITURE / FINISHES

Nero / Black RAL 9005	NR	BN	Bianco / White RAL 9016
Antracite / Anthracite	AT	MK	Moka
Corten	CT	RM	Rame / Copper
Ottone / Brass	OT	AL	Alluminio / Aluminium
Ottone brunito / Burnished brass	OTBR	TT	Titanio L55 / Titanium L55 Galvanica / Galvanic
Anodizzato Nero / Anodized black	AN	AA	Anodizzato Alluminio / Anodized aluminium
Anodizzato Bronzo / Anodized bronze	BRS	AC	Anodizzato Champagne / Anodized champagne
Cromo lucido / Polished chrome	CR	OR	Oro lucido / Shiny gold
Oro satinato / Satin gold	ORST	ORM	Oro rame / Copper gold
		CS	Custom

MATERIALI / MATERIALS

Corpo in alluminio tornito dal pieno, verniciabile in un'ampia gamma di colori. Adattatore per micro binario bassa tensione in materiale plastico.

Aluminum body turned from solid, paintable in a wide range of colors. Adapter for low micro voltage track in plastic material.

ELETTRONICA / ELECTRONICS

Led ad alto rendimento. Scheda di controllo interna all'adattatore del binario bassa tensione. Dimmerabile remoto DALI, PUSH, DMX, 0-10, 1-10 e TAGLIO DI FASE.

High performance LED. Control board inside the low voltage track adapter. Remote dimmable DALI, PUSH, DMX, 0-10, 1-10 and PHASE CUT.

