

SIDE 1/2



36°



36°

UP/DOWN

monoemissione




Corpo illuminante da parete, da esterno, dal design minimale, mono e biemissione. Verniciabile in un'ampia gamma di colori.

Wall-mounted, outdoor lighting body with a minimal design, single and double emission. Paintable in a wide range of colors.



bi-emissione



FINITURE / FINISHES

| | | | |
|-------------------------------------|-------------|-----------|----------------------------|
| Nero / Black RAL 9005 | NR | BN | Bianco / White RAL 9016 |
| Antracite / Anthracite | AT | MK | Moka |
| Corten | CT | RM | Rame / Copper |
| Ottone / Brass | OT | AL | Alluminio / Aluminium |
| Ottone brunito / Burnished brass | OTBR | CS | Custom |

| Code | XX (LED Color) | YY° (Optic) | ZZ (Power) | Flux |
|------|----------------|-------------|------------|----------|
| SDM | WW (3000K) | 36 | 05 (5 W) | 500 lm |
| SDB | NN (4000K) | | 10 (2x5 W) | 2x500 lm |

MATERIALI / MATERIALS

Corpo in alluminio pressofuso, verniciabile in un'ampia gamma di colori.

Injection moulding aluminum body, paintable in a wide range of colors.

ELETTRONICA / ELECTRONICS

Led ad alto rendimento. Dimmerabile TAGLIO DI FASE.

High performance LED. Dimmable PHASE CUT.


1

∅65mm



92,50mm

97mm



2

∅65mm



92,50mm

170mm

